

In the claims:

1. (previously presented) A program product for use by a wireless device in a wireless communications environment, the program product comprising a computer readable medium having embodied therein a computer program for storing data, the computer program comprising:

logic for associating the wireless device with a current access point;

logic for ascertaining, by the wireless device, whether the wireless device should attempt to associate with an alternative access point, the ascertaining logic operating at least in-part on indications of a level of attenuation of signal strength of transmissions from the alternative access point where the alternative access point transmits at less than full power, and

logic for requesting association with the alternative access point if it is ascertained that the wireless device should attempt to associate with said alternative access point.

2. (previously presented) The program product of claim 1 further comprising:

logic for automatically collecting, by the wireless device, information about the alternative access point, including an indication of the level of attenuation.

3. (previously presented) The program product of claim 2 wherein the logic for ascertaining ascertains that the wireless device should attempt to associate with the alternative access point if the alternative access point is closer than the current access point in terms of a biased distance which accounts for AP loading.

4. (previously presented) The program product of claim 3 wherein the logic for ascertaining ascertains that the alternative access point is closer than the current access point by:

calculating a first biased distance between the wireless device and the current access point based on “x” samples;

calculating a second biased distance between the wireless device and the alternative access point based on “y” samples where “y” is less than “x”; and

ascertaining that the alternative access point is closer than the current access point if the second biased distance is less than the first biased distance.

5. (previously presented) The program product of claim 3 wherein the logic for requesting association requests association by sending a message to the alternative access point.

6. (previously presented) The program product of claim 1 wherein the ascertaining logic also employs maximum potential signal strength of the alternative access point.